Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

SCENICVIEW A17-1

Value Line TFT display – Enter the world of LCD displays

Issue April 2005

Pages 2

With the SCENICVIEW Value Line TFT displays Fujitsu Siemens Computers leads the way to the future by creating convenient and reliable working environments. LCD TFT technology stands for top picture quality, ergonomics and ideal environment compatibility.

The SCENICVIEW A17-1 is the ideal choice for entering the world of professional LCD displays. The space saving design offers a new scope for arranging a workplace. With its low power consumption, the SCENICVIEW A17-1 saves energy and environment.

Reliability

- Outstanding quality and stability
- Low power consumption
- Power management according to EPA

Usability

- Administrator is able to read inventory data
- Space saving design
- Auto-adjust
- Tilt-base
- Integrated power supply
- Ease-of-use menu
- Plug & Play
- Analog interface
- Standardised mounting interface

Diversity

- Display portfolio for differentiated demands
- Comparable with 19-inch CRT display

Ergonomics

- Optimum flicker-free and distortion-free ergonomics
- Wide viewing angle
- High contrast and excellent focus
- Environmental friendly with low-radiation
- Immunity to external electromagnetic fields

Visible screen diagonal	17 inch (43 cm)
Graphics display (dependent on graphics processor)	
Pixels	1280 x 1024
Pixels *)	1024 x 768
Pixels *)	800 x 600
Pixels *)	640 x 480
*) expanded	
Text display (dependent on graphics processor)	
Pixels (max. 70 Hz)	720 x 400
Picture size	338 x 270 mm
Pixel Pitch	0.264 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz
Brightness typical	250 cd/m^2
Contrast typical	500 : 1
Viewing angle typical	
Horizontal	140°
Vertical	125°
Response time typical	12 ms
Plug & Play	VESA DDC 2B
Ease-of-use menu	
Direct key access	auto adjust, brightness menu, OSD menu-lock
Brightness / contrast	brightness, contrast
Image adjust	H, V position, clock, phase
Color	6500 K, 9300 K, native, customer settings
OSD setup	language, position
Advanced	resolution notifier, factory recall
Information	display mode
Tilt Base	
Tilt angle	-5° / +25°

Electrical values	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw typical	
Operating	28 W
Power save mode (Standby-, Suspend- and Off- mode)	1 W
Soft switch off (front)	<1 W
Protection class	1
Temperatures / dimensions / weight	
Ambient temperature (to IEC721)	
Recommended range	15°C to 35°C
Limit	0°C to 35°C
Dimensions with base (H x W x D)	404 x 375 x 174 mm
Dimensions without base (H x W x D)	343 x 375 x 57 mm
Weight unpacked / packed	4.2 kg / 5.2 kg
without base	3.5 kg
Reliability typical	
MTBF (demonstrated)	70,000 h
Lifetime of LCD (brightness > 50% of original brightness)	50,000 h
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and suppression	CE certification according RFI to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'03
Video input	1 x D-SUB analog
Data cable (1.8 m) detachable on display	D-SUB (15-pin) analog
Power cable (1.8 m)	for wall socket Euro-Schuko-Type CEE7
Integrated power supply	
Plug type on display side	IEC-320-C13
Special features	Kensington Lock prepared, standardized mounting, interface according, VESA FPMPMI (100mm)
Order code	S26361-K1017-V150

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Copyright © Fujitsu Siemens Computers,04/2005

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp